




total access control

1834 PC PROGRAMMABLE TELEPHONE ENTRY SYSTEM



OPERATING INSTRUCTIONS

1. Use # TO Z Buttons to Enter Name and Code Number to System. Name and Code Number are Stored and in Appearance. Press * to End Name and Code Number.
2. To Call Guest Code Number, Lift Receiver, Press *#* Guest Code, Press #. Press * to End.
3. Press on Green Buttons and Tone.



features

- Provides visitor access control into apartment buildings, gated communities, condominiums, office buildings, factories and industrial sites
- PC programmable system allows programming from a pc via modem or RS-232 interface. DoorKing Remote Account Manager and Transaction Analysis software included
- Visitors use the 1834 to communicate with a resident, who can then grant or deny them access from their touch-tone telephone
- Large A and Z scroll buttons and one touch CALL button makes system operation quick and easy

1834



total access control

TECH SPECS

electrical requirements

16 VAC, 20 VA System power (350 ma)
U.L. listed power transformers provided
Ringer equivalence: 0.0A Jack Type: RJ11C or W

communication

Full duplex Hands free
Optional handset available (ADA compliant)
surface or flush mount only

operating temp

10°F to 145°F
-12°C to 62°C
Optional heater kit available for colder climates

capacity

Max 3000 phone numbers, 10 area codes
8000 event transaction memory
4 digit entry codes same as telephone number memory

door/gate control

2 doors and or gates

advanced features

Live Transactions (requires RS-232 connection)
Programmable directory codes can be set from 1 to 4 digits in length
10 & 11 digit dialing capability
32 holiday schedules
Built in clock/calendar
8 hold open time zones

programming methods

Program via dial-up modem or RS232 interface with included programming and transaction analysis software
Other programming methods include system keypad and remotely from a touch tone telephone

display & mounting styles

Single line 20 character super-twist LCD-1/2 inch characters
Surface, flush or wall mount

listing

FCC (US) DUF6VT-12874-OT-T
DOC (CAN) 1736 4528 A
Complies with UL 294 ETL Listed

dimensions

Surface mount: Height: 13 inches
Width: 11 1/4 inches
Depth: 4 3/4 inches @ top 3 3/4 inches @ bot
Flush mount unit: Height: 13 1/2 inches
Width: 12 inches Depth: 2 1/2 inches
Flush mount kit: Height: 15 inches
Width: 13.25 inches Depth: 3.5 inches
Wall mount: Height: 15 inches
Width: 13.25 inches Depth: 3.5 inches
Shipping Weight: Approximately 15-20 lbs
Warranty: 2 year limited factory warranty


THE MODEL 1834 is an ideal telephone entry system that is suited for large applications that have a separate access control system, or in applications that require telephone entry access only. Visitors are easily identified by voice communication (a CCTV camera option provides visual ID as well) and can be granted or denied access directly from a touch-tone telephone.



*Requires purchase of additional CCTV equipment

Complete Access Control System

controls visitor access into a gated community, apartment complex, office building or industrial sight. Visitors use the phone system to communicate with a resident who can grant or deny them access via their own telephone.



telephone access systems use a modular design concept that makes installation and service easy



3 mounts
Surface, flush, and wall mounts are available



large scroll
buttons simplifies system operation



LCD display
big half inch characters

LIVE TRANSACTIONS

View activity AS IT HAPPENS on your computer display!

